

MULTIFUNCTION CONTROLLER CX-804

CX-804 multifunction controller is one of the devices of new generation representing wide range of features and applications. It enables simultaneous measurement in 1 to 4 measurement points. The readouts are displayed simultaneously on graphic display. The information about the relays' status is also given.



High measurement accuracy and stability have been provided.

Thanks to the modern electronic components the controller's memory has become fully independent from the power supply.

Depending on the needs the controller may be prepared and programmed for measurements of the chosen functions.

It is possible to choose up to 4 measurement functions and make simultaneous measurements with use of suitable types of electrodes and sensors.

Depending on needs, the device is able to measure pH, redox, conductivity, oxygen dissolved in water, relative air humidity and temperature. It is possible to choose up to 4 measurement functions and make simultaneous measurements with use of suitable types of electrodes and sensors. The device may be also used for measurement in one function, but in 4 points (e.g. pH).

The controller is a stationary device in housing resistant to humidity (IP-65).

Easy and intuitive in use.

CX-804 cooperates with several kinds of immersible or flow-through heads. The choice of suitable head, sensors and electrodes has to be agreed individually with the user, because it depends on the chosen type of measurement function, working conditions and parameters of the measured liquid.

The signal from the electrodes or sensors is amplified in pre-amplifier placed in the head or next to it in case of flow heads.

After converting the signal from electrodes and sensors, the device calculates it to the measured function units and shows the readout on the display. At the same time, the measurement signal is compared with set alarm threshold (upper or lower) and in case of exceeding it, the relay in appropriate channel is switched. The device enables entering the threshold value of the measured function separately for each channel and sending the information about measurements in all channels to the computer.

Each channel is additionally equipped with isolated current loop outputs at 0 - 20 or 4 - 20 mA.

Isolated digital outputs: RS-485, MODBUS (ASCII and RTU).

The device is equipped with two relays controlling valves for each channel.

Contrary to the controllers of 801 series, **CX-804** does not have PID controlling option.

It is possible to calibrate the meter without the need of disconnecting the outputs.

The controller is powered with standard 230V voltage, which is galvanically isolated from the input clamps. It is possible to use different power supply voltage: 110/230/24V AC, 12 – 24V DC (optionally).

The device is easy to operate, has an English menu. It is equipped with a collective optical signalisation of working correctness and the progress of the controlling process.

The device is equipped with real time clock with date and low power supply level signalisation system.

It is possible to connect to the remote panel (keyboard with display), which enables to control the device from up to 1 km distance.

24 months of warranty, quick warranty and after-warranty service.

CE Certificate.

TECHNICAL DATA

pH measurement

Measurement value	pH, temperature
pH range	0 ÷ 14 pH
Resolution	0.01 pH
Accuracy*	0.02 pH ±1 digit
Input impedance	>10 ¹² Ω
Temperature measuring range**	-50 ÷ 200 °C
Temperature compensation	automatic
Temperature compensation range	-5 ÷ 130 °C
Sensor calibration	1,2 or 3 point value of the solutions set in a given range

Redox potential measurement

Measurement value	mV, temperature
pH range	-2000 ÷ 2000 mV
Resolution	1 mV
Accuracy*	± 1 mV ±1 digit
Input impedance	>10 ¹² Ω
Temperature measuring range**	-50 ÷ 200 °C

Conductivity measurement

Measurement value	conductivity, temperature
Range	version for measurements in clean water: 0 ÷ 9999 µS/cm version for measurements in sewage, waste water, etc.: 0 ÷ 999.9 mS/cm
Resolution	depending on the range 0.1 µS/cm to 0.1 mS/cm
Accuracy*	0,5 % ± 1 digit
Temperature compensation	automatic
Temperature compensation range	-5 ÷ 70 °C
Temperature measuring range**	-50 ÷ 200 °C
K constant range	0.005 ÷ 20.000 cm ⁻¹
α coefficient range	0.00 ÷ 10.00 %/°C
Sensor calibration	1 point by entering the constant K of the cell or with use of the standard solution.

Oxygen dissolved in water

Measurement value	O ₂ , temperature
Oxygen O₂ %	0 ÷ 600 %
Oxygen O₂ mg/l	0 ÷ 60 mg/l
Resolution	0.1 % or 0.01 mg/l
Accuracy***	±0.2 %, ± 0.02 ±1 digit
Temperature range**	-50 ÷ 200 °C
Temperature compensation	automatic
Temperature compensation range	0 ÷ 40 °C (for mg/l measurement)
Sensor calibration	1 or 2 point

Relative air humidity (RH)

Measurement value	RH, temperature
Range %	0 ÷ 100% / -40 ÷ 70 °C
Temperature range	-40 ÷ 70 °C
Temperature compensation range	-20 ÷ 70 °C
Resolution	0.1%
Accuracy	in the range 10 ÷ 90% RH: ±2%, beyond this range: ±4% / temperature: ±1 °C

Temperature (as separate function)

Measurement value	temperature
Range	-70 ÷ 300 °C
Resolution	0,1 °C
Accuracy****	±2 °C

Other data

Temperature accuracy*	±0.2 °C
The relays' parameters	2A/250VAC/30VDC
Measurement input	isolated
Data-logger output	isolated, 0 ÷ 20 mA or 4 ÷ 20 mA
Temperature data-logger output	isolated, 0 ÷ 20 mA or 4 ÷ 20 mA
RS485 output	isolated
Maximal RS485 connection length	1000 m
Maximal cable length between preamplifier and controller	200 m
Maximal distance between sensor and preamplifier	10 m
Power supply	240 V 50 Hz, for a special order: 170VAC÷250VAC, 24VDC/24 VAC
Isolation class	PN-83/T-06500
Radio-electric interference	N level
Dimensions (L x W x H)	215 x 215 x 95 mm
Weight of controller / preamplifier	1350 g / 150g
Ambient temperature	-25 ÷ 40 °C
Atmospheric humidity / pressure	Max. 80% / 80 ÷ 110 kPa
Atmospheric aggressivity level	N/2/AG-U/C

* The accuracy of the meter only.

** Temperature measuring range limited to the temperature operating range of the head or electrode.

*** The accuracy of the meter only. With **COG-1** or **COG-2** oxygen sensor the accuracy at calibration temperature: ±1 %. By the difference ±5 °C accuracy: ±3 %, by the difference ±10 °C accuracy: ±5 %.

**** The accuracy of the meter only. The total error includes the meters and probe's accuracy. In the range 0 ÷ 100 °C the acceptable error of the probe with **Pt-1000B** resistor:±0.8 °C, with **Pt-1000A** resistor: ±0.35 °C.

ELMETRON® Sp. j.

41-814 Zabrze. Witosa 10 POLAND

tel. +48 32 2738106

www.elmetron.pl e-mail: info@elmetron.com.pl